



***SRT 5410***

**HD**  
HIGH DEFINITION

**HIGH DEFINITION  
DIGITAL TERRESTRIAL  
TELEVISION RECEIVER**

- **MPEG-4 HD/H.264 Compliant**
- **1080i / 720p / 576p/i Video Resolution Output Capabilities**
- **USB 2.0 Host for Firmware Update**
  
- **HDMI Output**
- **Component Video: Y, Pb & Pr Outputs**
- **Digital Audio Optical Output**
- **16:9 Full Screen, 4:3 Letterbox & Full Screen**
- **Electronic Program Guide**
- **Closed Captions & Teletext**
- **Auto & Manual Channel Search**
- **Favourite Channel List**
- **DVB/T, MPEG-2/4, H.264 Compliant**
- **COFDM Demodulation**



 **STRONG**

*not just by name*



## Tuner

Guard Internal Modes	: 1/32, 1/16, 1/8, 1/4 Active Symbol Duration	Signal Level	: -78.5 - -25dBm
FEC Mode Rates	: 1/2, 2/3, 3/4, 5/6, 7/8	Input Impedance:	: 75
Input Connector	: IEC 169-2, Female	Wave Form	: OFDM
Frequency Range	: 174-862MHz	Carrier Mode	: 2K & 8K
Demodulator	: COFDM 2K/8K-Carrier		
Channel Bandwidth	: 7/8MHz Switchable by Software		

## MPEG TS A/V Decoder

Transport Stream Profile Level	: MPEG-2 ISO/IEC 13818-1	Audio Decoding	: MPEG/Musical Layer & Dolby Digital
	: MPEG-II MP@ML, MPEG-II MP@HL	Audio Mode	: Stereo / Joint Stereo / Mono
	: MPEG-IV AVC/H.264 MP@L4.0	Sampling Rate	: 32KHz, 44.1KHz & 48KHz
Video Resolution	: 720 x 576i/p, 1280 x 720p & 1920 x 1080i Selectable	Input Rate	: Max. 15 Mbit/s
Video Formats	: 4:3 Letterbox, 4:3 Pan & Scan, 16:9 Pillarbox & 16:9 Full Screen		

## A/V Input/Output

Video Output	: RCA/Cinch Y, Pb, Pr (Component)	S/PDIF	: Digital Audio Optical Output
	: RCA/Cinch (CVBS)	Audio	: RCA/Cinch L/R
Digital A/V Output	: HDMI 1.2 (High Definition Multimedia Interface)		

## Data Input/Output

USB	: 2.0 Host
-----	------------

## System Resources

Main Processor	: STi7101 32bit Super Scalar RISC CPU - 400 Dhrystone 2.1MIPS@266MHz
Flash ROM	: 64Mbit
DDR DRAM	: 1024Mbit

## Power Supply

Input Voltage	: AC 100-240V~, 50/60Hz	Power Consumption	: Max. 20 W
Type	: SMPS (Switching Mode Power Supply)	Protection	: Separate Internal Fuse

## Physical Specifications

Size (W x D x H)	: 360 x 240 x 69 mm
Weight	: 2.0 Kg
Operating Temperature	: 0°C ~ +50°C
Storage Temperature	: -40°C ~ +70°C

E. & O. E.

## DISTRIBUTED BY:

