

## SPT-800

### Symmetrical Mono Hybrid Amplifier



The best of the bunch. The pre-amplification is by Russian 6922 valves and two 6N6 valves. Eight high-power transistors deliver a powerful 200W at 8 Ohm. The 500W transformer and elcos with a total of 80,000 uF offer excellent bass. The new FET mains connector ensures high signal noise distance in this end stage, very little distortion and a clear and open sound.

Vincent - born in Germany 1995



#### Technical details

Frequency response: 10 Hz - 50 kHz +/- 0.5 dB,  
Nominal Output Power RMS/8 Ohm: 200W,  
Nominal Output Power RMS/4 Ohm: 320W  
Class A/8 Ohm: 20W, Total harmonic distortion: < 0.1% (1 kHz, 1 Watt),  
Input sensitivity: 1,1V, Signal-Noise ratio: > 90 dB  
Input impedance: 47 kOhm, Inputs: 1 x RCA, 1 x XLR  
Outputs: 2 x 2 Speaker Terminal (A & B), Mains supply: 230 V/50 Hz  
Colour: black/silver, Weight: 18 kg, Dim. (WxHxD): 210x265x400 mm  
Tubes: 1 x 12AU7, 1 x 6922, 2 x 6N6  
Power Control Switched output voltage: Trigger 12 V (Input/Output)