

SERIES



AUDIO TECHNOLOGY



THE ULTIMATE IN RELIABILITY  
PERFORMANCE AND TECHNOLOGY

## AARON ATS RANGE OF SPEAKERS



specifications	ATS-1	ATS-3	ATS-4	ATS-5
frequency response	55Hz - 23KHz ±3db free field	38Hz - 23KHz ±3db free field	35Hz - 23KHz ±3db free field	28Hz - 23KHz ±3db free field
recommended amplifier power	30 - 100W per channel undistorted	30 - 140W per channel undistorted	30 - 160W per channel undistorted	30 - 200W per channel undistorted
sensitivity	89db	93db	93db	93db
nominal impedance	8 ohms	6 ohms	6 ohms	6 ohms
bass alignment	low Q ratio	low Q ratio	low Q ratio	low Q ratio
crossover frequency	3.5KHz	3.5KHz	800Hz / 5KHz	800Hz / 5KHz
tweeter	25mm tear drop	25mm tear drop	25mm tear drop	25mm tear drop
mid range			136mm dual laminare cone	136mm dual laminare cone
woofer	173mm dual laminare cone	173mm dual laminare cone	2 x 173mm dual laminare cone	2 x 213mm dual laminare cone
cabinet dimensions	385mm H 210mm W 245mm D	800mm H 210mm W 405mm D	920mm H 210mm W 405mm D	945mm H 250mm W 405mm D
enclosure finish	black or beech	black or beech	black or beech	black or beech
weight	6kg	15kg	18kg	21kg



AARON LOUDSPEAKERS  
BETETEC INDUSTRIES PTY. LTD  
17 DEHAVILLAND CRESCENT BALLINA NSW 2478 AUSTRALIA  
TEL 0266 860 277  
WEB: [www.aaronhifi.com.au](http://www.aaronhifi.com.au) EMAIL: [speakers@aaronhifi.com.au](mailto:speakers@aaronhifi.com.au)